

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: HIGH TEMPERATURE THREAD SEALANT 50ML
Item No: 59235
Product Type: Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
POLYGLYCOL DIMETHACRYLATE 25852-47-5	20-40	Not listed	Not Listed
POLYESTER RESIN MIXTURE	10-30	Not listed	Not Listed
SILICA, MICA 12001-26-2	10-30	3 mg/m ³	20 mppcf TWA
POLYETHYLENE GLYCOL ESTER 18268-70-7	<20	Not listed	Not Listed
OCTANOL 111-87-5	<10	Not listed	Not Listed
POLYTETRAFLUOROETHYLENE 9002-84-0	<5	Not listed	Not Listed
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	<5	10 mg/m ³	10 mg/m ³ total dust
TITANIUM DIOXIDE 13463-67-7	<3	10 mg/m ³	15 mg/m ³ TWA (total dust)
PROPYLENE GLYCOL 57-55-6	<3	Not listed	Not Listed
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<2	Not listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May cause eye and skin irritation. May cause skin sensitization. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Repeated skin contact may cause allergic skin reactions. May cause redness to eyes and irritation to nasal passages.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
POLYTETRAFLUOROETHYLENE 9002-84-0	<5			Group 3 Supplement 7, 1987; Monograph 19, 1979
TITANIUM DIOXIDE 13463-67-7	<3	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°):	>200° F TCC
Recommended Extinguishing Media:	Water fog, carbon dioxide, foam, dry chemical.
Special Fire-Fighting Procedures:	Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion:	Irritating vapors, Oxides of carbon
Unusual Fire/Explosion Hazards:	None
Lower Explosive Limit:	1.0: Octanol
Upper Explosive Limit:	8.0: Octanol

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:	Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.
--------------------------	---

7. HANDLING AND STORAGE

Storage:	Store below 100 degrees F. Keep in cool and dark place. Avoid direct sunlight.
Handling:	Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses.
Skin:	Neoprene or nitrile gloves recommended.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White paste
Odor:	MILD
Boiling Point:	>300°C.
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	1.2
VOC Content(Wt.%):	2.8%
Vapor Pressure:	Not determined
Vapor Density (Air=1):	Heavier than air
Evaporation Rate:	Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	WILL NOT OCCUR.
Incompatibilities:	Metal salts, heat and amines.
Conditions to Avoid:	Heat
Hazardous Products of Combustion:	Irritating vapors, Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number:	NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
Domestic Ground Transport

Product Name: HIGH TEMPERATURE THREAD
SEALANT 50ML

Item No: 59235

14. TRANSPORTATION INFORMATION

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: August/14/2007

Revision 3

Number:

Telephone No.: 1-87-Permatex (877) 376-2839