

Material Safety Data Sheet OSHA's Hazard Communication Standard U.S. Department of Labor

29 CFR 1910.1200 OMB No. 1218-0072

Identity # Name K&N Grease 6oz; Part #99-0703-1 and 99-0704

Section 1

Manufacture's Name -Address - 310 Reed Circle City - Corona State - CA U.S. Continental Marketing

Emergency Phone (Chemtrec) 1-(800)-424-9300

Daytime Phone - 1-(951)- 808-8888 Contact Person - Robert Munion

Date Prepared- 12/11/2007

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components CAS# OSHA PEL ACGIH TLV Weight% (Optional)

None NONE NONE NONE

Note: Part #99-0703-1 and 99-0704

VOC Content- 0 g/L

Section 3 - Physical/Chemical Characteristics

Boiling Point- >212 F Specific Gravity- .839

Vapor Pressure - Not Tested Melting Point - Not Tested Evaporation Rate - Not Tested

Solubility In Water- Insoluble

Appearance and Odor- Brown, Bland Odor

Section 4 - Fire and Explosion Hazard Data

Flash Point- 325 F Flammable Limits - Not Tested

LEL- Not Tested UEL- Not Tested

pH- NOT TESTED

NFPA Hazard Rating - H F R S HMIS Hazard Rating - H F R $(0-Least, 4-Extreme \ 1 \ 0 \ 0 \ 0 \ 1 \ 0 \ 0$

Extinguishing Media- CO2, DRY FOAM

Special Fire Fighting Procedures NONE

Unusual Fire and Explosion Hazards NONE

Section 5 - Reactivity Data

Stability - Stable

Conditions to Avoid - None

Incompatible Materials to Avoid- WATER, STRONG OXIDIZERS

Hazardous Decomposition or Byproducts- CO, CO2

Hazardous Polymerization NONE

Conditions to Avoid- None

Section 6 - Health Hazard Data

Routes of Entry Inhalation? - Possible Skin? - Possible Ingestion? - Possible

Health Hazards - Same as Signs and Symptoms of Exposures

Note - All Chemicals in this Product are Found on the TSCA Inventory List.

OSHA Carcinogenicity? - None; NTP? - None; IARC Monographs? - None.

Signs and symptons of over exposure:

Eyes - Burning Sensation

Skin- Slight Irritation

Ingestion- Do Not Induce Vomitting, Call Physician

Inhalation- Not Expected To Be A Problem

Medical Conditions Generally Aggraved by Exposure - Same as Signs and Symptoms of Over Exposure.

#

Emergency and First Aid Procedures

Eyes - Flush With Water For 15 Minutes. If Irritation Persists, Call Physician.

Skin- Wash Off With Soap & Water

Ingestion- Do Not Induce Vomitting, Call Physician

Inhalation- Get Person to Fresh Air If Unconscious, Call Physician

Section 7 - Precautions For Safe Handling and Use.

Steps to be taken in case material is released or spilled - Soak up with inert, absorbant material. Scoop up and place in a proper waste disposal container.

Waste Disposal Method - Dispose of in accordinance with state and local regulations. Precautions To Be Taken In Handling and Storing - Store in a cool, dry place, out of direct sunlight. Do not freeze, less than or equal to 32 F, or heat above 110 F.

Other Precautions - Keep out of reach of children. Follow directions on the container for proper use of this product.

Section 8 - Control Measures

Respiratory Protection - Open all doors and windows. "If" and when there is an exposure, and it is above the TLV or PEL, a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CRF 1910.134, is required.

Local Exhaust - If Available Special - None Ventilation Mechanical - If Available Other - None

Protective Gloves- None

Eve Protection-Glasses, Goggles

Other Protective Clothing or Equipment None

Work Hygenic Practices - Use common sense and care around chemicals. Never mix chemicals. Consult your supervisor for other practices. All practices depend on your specific business. Directions for use are normally found on label which will dictate engineering and control measures.

Other Special Requirements

Note: USCM believes the data set forth are accurate. USCM makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion