

Permatex, Inc.  
10 Columbus Blvd.  
Hartford, CT 06106 USA  
Telephone: 1-87-Permatex  
(877) 376-2839  
Emergency: 800-255-3924  
International Emergency: 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** CERAMIC EXTREME BRAKE PARTS LUBRICANT 8 FL.OZ  
**Item No:** 24125  
**Product Type:** Lubricant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
SYNTHETIC BASE OILS TRADE SECRET	>90	Not listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness.

**Medical Conditions Recognized as Being Aggravated by Exposure:** Preexisting skin disorders.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If signs of irritation or toxicity occur seek medical attention.  
**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** >500°F COC  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Special Fire-Fighting Procedures:** Treat as oil fire. Firefighters should wear self-contained breathing apparatus.  
**Hazardous Products of Combustion:** Oxides of carbon  
**Unusual Fire/Explosion Hazards:** None  
**Lower Explosive Limit:** Not determined.  
**Upper Explosive Limit:** Not determined.

### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

### 7. HANDLING AND STORAGE

**Storage:** Store away from heat.  
**Handling:** Avoid contact with skin and eyes. Wash thoroughly after handling. Product may cause surfaces to become slippery.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General ventilation is usually adequate.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Respiratory Protection:** Not normally necessary.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Purple semi-solid  
**Odor:** MILD  
**Boiling Point:** Not determined.  
**pH:** Does not apply  
**Solubility in Water:** Insoluble  
**Specific Gravity:** 0.94  
**VOC Content(Wt.%):** None  
**Vapor Pressure:** Not Determined  
**Vapor Density (Air=1):** > 1 (air = 1)  
**Evaporation Rate:** <1 (butyl acetate = 1)

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** WILL NOT OCCUR.  
**Incompatibilities:** Strong oxidizers  
**Conditions to Avoid:** Welding  
**Hazardous Products of Combustion:** Oxides of carbon

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

**DOT Shipping Name:** Unrestricted  
**Hazard Class:** None  
**UN/ID Number:** None  
**Marine Pollutant:** None

### **IATA**

**Proper Shipping Name:** Unrestricted  
**Class or Division:** None  
**UN/ID Number:** None

### **IMDG**

**Proper Shipping:** Unrestricted  
**Hazard Class:** None  
**UN Number:** None

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

### **CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present.

### **TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**Product Name:** CERAMIC EXTREME BRAKE PARTS  
LUBRICANT 8 FL.OZ

**Item No:** 24125

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, INSTABILITY 1 .

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** May/27/2008

**Revision** 1

**Number:**

**Telephone No.:** 1-87-Permatex (877) 376-2839