

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 10/01/2008

1. PRODUCT IDENTIFICATION			CHEMICAL RESPONSE CARD: 00	
1.1	Product Name:	SHELL ATF 134 TRANSMISSION OIL	RESPONSE TEAM PPE:	
1.2	Chemical Name:	See ingredients listed in section 3	WHMIS:	
1.3	Synonyms:	None reported by the manufacturer	HEALTH:	0
1.4	Trade Names:	None reported by the manufacturer	FLAMMABILITY:	1
1.5	Product Use:	Automotive – Lubricant	REACTIVITY:	0
1.6	Distributor's Name:	WorldPac, Inc.	PERSONAL PROTECTION:	B
1.7	Distributor's Address:	37137 Hickory Street, Newark, CA 94560, USA		
1.8	Business Phone:	+ 1 (510) 608-5525		
1.9	Emergency Phone:	CHEMTREC +1 (800) 527-3887 / +1 (703) 527-3887		

2. HAZARD IDENTIFICATION

2.1	Hazard Identification: This product is NOT classified as a HAZARDOUS SUBSTANCE or as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). Combustible liquid.						
2.2	Routes of Entry:	Inhalation:	NO	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure: EYES: This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. SKIN: This product can cause mild, transient skin irritation with short-term exposure. INGESTION: If swallowed, no significant adverse health effects are anticipated. Ingestion can cause a laxative effect. INHALATION: No significant adverse health effects are expected to occur upon short-term exposure to this product.						
2.4	Symptoms of Exposure: EYES: Irritation, redness, and watering. SKIN: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.. INGESTION: Laxative effects. Gastrointestinal discomfort, nausea and/or diarrhea. INHALATION: May cause irritation to the upper respiratory system.						
2.5	Acute Health Effects: EYES: Slightly irritating, but will not injure eye tissue. SKIN: Low toxicity. Frequent or prolonged contact may irritate the skin such as oil acne/ folliculitis. INGESTION: Low toxicity. Laxative effects. Gastrointestinal discomfort, nausea and headache. INHALATION: Negligible. At elevated temperatures or through mechanical action, may form vapours, mists or fumes that may be irritating to the eyes, nose, throat and lungs.						
2.6	Chronic Health Effects: None reported by the manufacturer.						
2.7	Target Organs: None reported by the manufacturer.						
2.8	Toxicological Properties: None reported by the manufacturer.						

3. COMPOSITION & INGREDIENTS

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)								
					ACGIH		NOHSC			OSHA			OTHER
					TLV	STEL	ppm	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	
DISTILLATES PETROLUUM SOLVENT DEWAXED HEAVY PARAFFINIC	64742-65-0	PY8038501	265-169-7	< 30.0	NA	NA	NF	NF	NF	NA	NA	NA	
PROPRIETARY ADDITIVES	NA	NA	NA	< 3.0	NA	NA	NA	NA	NA	NA	NA	NA	


NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used. NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards | MSDS Revision: 1.0 | MSDS Revision Date: 10/01/2008

4. FIRST AID

4.1	<p>First Aid:</p> <p>EYES: Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness, or pain persists.</p> <p>SKIN: Remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods.</p> <p>INGESTION: Do not induce vomiting unless directed to by a physician. Give plenty of water to drink, unless directed to by a physician. Never give anything by mouth to a person who is not fully conscious. If large quantities are swallowed, seek medical attention immediately.</p> <p>INHALATION: In case of overexposure, move the person to fresh air. Give artificial respiration or oxygen if necessary, seek medical attention immediately.</p>
4.2	<p>Medical Conditions Aggravated by Exposure:</p> <p>Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin.</p>

5. FIRE & EXPLOSION HAZARDS

5.1	<p>Flashpoint & Method: 199 °C (390 °F), COC</p>				
5.2	<p>Autoignition Temperature: >320 °C (608 °F)</p>				
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	1.0	Upper Explosive Limit (UEL):	10.0
5.4	<p>Fire & Explosion Hazards: This material can burn but will not readily ignite.</p>				
5.5	<p>Extinguishing Methods: Dry chemical, carbon dioxide, foam, and water spray/fog. Fight small fires with sand or earth. DO NOT use water in a jet.</p>				
5.6	<p>Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. For safety reasons, unsuitable extinguishing agents do not use water with full water jet. Avoid spraying water directly into storage containers because of danger of boilover. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.</p>				

6. SPILLS & LEAKS

6.1	<p>Spills:</p> <p>Secure spill area, remove or minimize all sources of ignition, and maximize ventilation. Stop spill or leak at source if safely possible. Individuals involved in the cleanup must wear appropriate personal protective equipment. Recover free liquid or cover with inert absorbent material and place into appropriate container(s) for disposal. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers or any natural waterway or drinking supply. Contact appropriate local and/or provincial authorities for assistance and/or reporting requirements. For water spills, remove from surface by skimming or with suitable absorbents. If allowed by federal & provincial environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters. Consult an expert on disposal of recovered material. Ensure disposal on compliance with government requirements & secure conformity to local disposal regulations. Notify the appropriate federal & provincial authorities immediately. Take all additional action necessary to prevent & remedy the adverse effects of the spill.</p>
-----	---

7. STORAGE & HANDLING

7.1	<p>Work & Hygiene Practices:</p> <p>Use normal hygiene practices. Use skin protection cream for preventive skin protection. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking.</p>
7.2	<p>Storage & Handling:</p> <p>Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Store in containers or containers linings, use mild steel or high density polyethylene. Store between temperatures of 0-50°C, (32-122°F).</p>
7.3	<p>Special Precautions:</p> <p>Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.</p>

8. EXPOSURE CONTROL & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls:	The use of mechanical dilution ventilation is recommended to maintain airborne concentrations below the recommended occupational exposure limits, whenever this material is used in a confined space, is heated above normal temperatures or is agitated.
8.2	Respiratory Protection:	Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved independent air supply respirator should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).
8.3	Eye Protection:	Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is anticipated. Have suitable eye wash water available.
8.4	Hand Protection:	Use gloves constructed of impermeable and resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Use heat-protective gloves when handling product at elevated temperatures.
8.5	Body Protection:	None required. Avoid prolonged and/or repeated skin contact.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.853
9.2	Boiling Point:	> 280 °C (536 °F)
9.3	Melting Point:	-42 °C (-44 °F)
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure @ 20°C:	< 0.5 Pa / 68 °F
9.6	Molecular Weight:	NA
9.7	Appearance & Color:	Red liquid
9.8	Odor Threshold:	Slight hydrocarbon odor
9.9	Solubility:	Negligible
9.10	pH:	NA
9.11	Viscosity:	NA
9.12	Coefficient Oil/Water Distribution:	NA
9.13	Additional Information:	Pour Point: -51 °C (-60 °F)

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions.
10.2	Decomposition Products:	None expected to form during normal storage.
10.3	Polymerization:	NA
10.4	Conditions to Avoid:	Open flames, sparks and high heat and direct sunlight.
10.5	Incompatible Substances:	Strong oxidizing agents.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 10/01/2008

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data:	No eye or skin irritant effect, also no sensitization effect known.
11.2	Acute Toxicity:	Oral, expected to be low toxicity: LD50 > 2000mg/kg, Rat. Dermal, expected to be low toxicity: LD50>2000mg/kg, Rabbit.
11.3	Chronic Toxicity:	NA
11.4	Suspected Carcinogen:	No
11.5	Reproductive Toxicity:	
	Mutagenicity:	This product is not expected to cause mutagenic effects in humans.
	Embryotoxicity:	This product is not expected to cause embryotoxic effects in humans.
	Teratogenicity:	This product is not expected to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not expected to cause reproductive harm in humans.
11.6	Irritancy of Product:	NA
11.7	Biological Exposure Indices:	NA
11.8	Medical Recommendations:	None reported by the manufacturer.

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl. Liquid under most environmental conditions. Floats on water. If it enters soil, it will absorb to soil particles and will not be mobile. Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment. Contains components with the potential to bioaccumulate.
12.2	Effect on Plants & Animals:	An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products.
12.3	Effect on Aquatic Life:	Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway can result in a loss of marine life or create an anaerobic environment. Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal & provincial hazardous waste laws.
13.2	Special Considerations:	If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local ordinance.



14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.



14.1	49 CFR (GND):	NOT REGULATED
14.2	IATA (AIR):	NOT REGULATED
14.3	IMDG (OCN):	NOT REGULATED
14.4	TDGR (CAN):	NOT REGULATED
14.5	ADR/RID (EU):	NOT REGULATED
14.6	SCT (MEX):	NOT REGULATED
14.7	ADGR (AUS):	NOT REGULATED

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 10/01/2008

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements: This product does not contain any substances subject to SARA reporting requirements.	
15.2	SARA Threshold Planning Quantity: NA	
15.3	TSCA Inventory Status: The components of this product are listed on the TSCA inventory.	
15.4	CERCLA Reportable Quantity (RQ): NA	
15.5	Other Federal Requirements: NA	
15.6	Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the priorities substances list.	
15.7	State Regulatory Information: This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. New Jersey Right to Know Chemical List - Distillates (petroleum), solvent-dewaxed heavy paraffinic Listed (64742-65-0) 15.00%; Pennsylvania Right-To-Know Chemical List - Distillates (petroleum), solvent-dewaxed heavy paraffinic Listed (64742-65-0) 15.00%	
15.8	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.	

16. OTHER INFORMATION

16.1	Other Information: NA	
16.2	Terms & Definitions: Please see last page of this MSDS.	
16.3	Disclaimer: This Material Safety Data Sheet complies with Health Canada's Workplace Hazardous Materials Information System (WHMIS) & U.S. OSHA's Hazard Communication Standard, 29 CFR §1910.1200. To the best of ShipMate's or Worldpac's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product. Contact the manufacturer for additional information.	
16.4	Prepared for: WorldPac, Inc. 37137 Hickory Street Newark, CA 94560 510-608-5525 phone 510-742-9262 fax http://www.worldpac.com/	
16.5	Prepared by: ShipMate, Inc. 780 Buckaroo Trail, Suite D Sisters, OR 97759 Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700 E-mail: shipmate@shipmate.com http://www.shipmate.com/	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health


FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or S.O.P. for special handling directions.

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-W	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₀₁ or TC, TC₀₁, LC₁₀, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
NOHSC	Australia National Occupational Health & Safety Code
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

C	E	F	N	O	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful